


Seals for Couplings Storz System

As flexible sealing elements, the seals of the Storz couplings are necessarily subject to greater wear. Although they are manufactured from high-grade elastomers in a wide range of materials to suit the intended application, they must therefore be occasionally replaced, to ensure a proper function of the coupling. All seals are injection-moulded and guarantee extreme dimensional accuracy and unchanging material constants, tensile strength, elasticity and dimensional stability. **All seals are sold in bags.**

Flat gaskets in nitrile rubber (white)



1704

Thread size	Pieces per bag	a x d x h (mm)	Weight per bag (kg)	Ident.-No.	Remarks
for adapters with female thread					
G 1	100	20 x 33 x 3	0,175		¹⁾ , DIN 14 306
G 1¼	20	32 x 42 x 3	0,060		
G 1½	50	41 x 48 x 3	0,155		
G 2	100	47 x 60 x 3	0,465		DIN 14 307
G 2½	100	66 x 76 x 3	0,500		DIN 14 308
G 3	100	78 x 88 x 3	0,565		
G 4	50	100 x 113 x 3	0,480		
G 4½	50	105 x 126 x 3	0,890		DIN 14 309
G 5	20	118 x 138 x 3	0,350		
G 6	10	152 x 164 x 4	0,190		
for end caps with male round thread					
Rd 50 x 1/6	1	46 x 58 x 4	0,010		¹⁾ , DIN 14 317
Rd 60 x 1/6	1	56 x 75 x 3	0,010		¹⁾ , NEN 33 74
Rd 65 x 1/6	1	61 x 78 x 4	0,010		¹⁾ , DIN 14 318

Thread size	Pieces per bag	a x d x h (mm)	Weight per bag (kg)	Ident-No.	Remarks
Rd 105 x 1/6	1	100 x 119 x 4	0,020		¹⁾ , DIN 14319

Other dimensions and styles on request.