

Symmetrical quick connections couplings with locking ring, only suitable for delivery operation. In Norway quick connection couplings Storz System are in use for suction operation.

- Aluminium alloys (A)
- Copper alloys (C)

Adapters NOR with female and male thread



1240 B

Nominal size	Lug spacing (mm)	Female thread	Male thread	Weight (kg)	Ident.No.	Remarks	Alloy
1 1/2"	50	G 1		0,150	60295833	LAS 3	A
1 1/2"	50	G 1		0,450	60295893	LAS 3	A
1 1/2"	50		G 1 A	0,150	30382433	LAS 3	A
1 1/2"	50		G 1 A	0,450	30382493	LAS 3	A
1 1/2"	50	G 1 1/4		0,150	30399233	LAS 3	A
1 1/2"	50	G 1 1/4		0,450	30399293	LAS 3	A
1 1/2"	50		G 1 1/4 A	0,150	30399433	LAS 3	A
1 1/2"	50		G 1 1/4 A	0,450	30399493	LAS 3	A
1 1/2"	50	G 1 1/2		0,200	60295933	LAS 3	A
1 1/2"	50	G 1 1/2		0,600	60295993	LAS 3	A
1 1/2"	50		G 1 1/2 A	0,200	60537533	LAS 3	A
1 1/2"	50		G 1 1/2 A	0,600	60537593	LAS 3	A
1 1/2"	50	G 2		0,250	30399333	LAS 3	A
1 1/2"	50	G 2		0,650	30399393	LAS 3	A
1 1/2"	50		G 2 A	0,250	30399533	LAS 3	A
1 1/2"	50		G 2 A	0,650	30399593	LAS 3	A
2"	66		G 1 1/2 A	1,200	60554893	LAS 2	A
2"	66	G 2		1,200	40421695	LAS 2	A

Nominal size	Lug spacing (mm)	Female thread	Male thread	Weight (kg)	Ident.No.	Remarks	Alloy
2"	66		G 2 A	1,200	60296193	LAS 2	A
2½ "	83	G 1		0,530	60652933	LAS 1	A
2 ½"	83	G1½		0,565	40447533	LAS 1	A
2 ½"	83	G1½		1,600	40447593	LAS 1	A
2 ½"	83		G1½ A	0,685	60435933	LAS 1	A
2 ½"	83		G1½ A	2,475	60435993	LAS 1	A
2 ½"	83	G 2		0,580	40346333	LAS 1	A
2½ "	83	G 2		1,835	40346393	LAS 1	A
2 ½"	83		G 2 A	0,550	60296233	LAS 1	A
2 ½"	83		G 2 A	1,600	60296293	LAS 1	A
2 ½"	83	G 2½		0,600	40347533	LAS 1	A
2 ½"	83	G 2½		1,850	40347593	LAS 1	A
2 ½"	83		G 2½ A	0,540	40432733	LAS 1	A
2 ½"	83		G 2½ A	1,500	40432793	LAS 1	A
2 ½"	83	G 3		0,760	60296433	LAS 1	A
2 ½"	83	G 3		2,100	60296493	LAS 1	A
2½ "	83		G 3 A	2,145	60654293	LAS 1	A