


Clamp fittings with threaded tail useable for pipes, fittings and appliances, when these appliances and fittings are to be held in a certain position i.e. when they must not turn during coupling.

- Aluminium alloys (A)
- High grade steel (St)

Clamp fittings swivelling with female threaded tail end



1100



1100

Nominal size	Lug spacing b (mm)	Inside dia. d (mm)	Female thread W	Face-to-face length L (mm)	Weight (kg)	Ident.No.	Remarks	Alloy
52=C	66	34	G 1 ¼	34	0,365	50237433		A
52=C	66	34	G 1 ¼	34	0,365	60361033	with locking device	A
52=C	66	40	G 1 ½	45	0,380	50195833		A
52=C	66	40	G 1 ½	45	0,400	60452233	with locking device	A
52=C	66	45	G 2	68	0,435	40269133		A
52=C-DS	66	45	G 2	51	0,900	40412846		A
75=B	89	45	G 2	68	0,500	60151733		A
75=B	89	45	G 2	68	0,720	60445233	with locking device	A
75=B	89	65	G 2 ½	49	0,560	50195933		A
75=B-DS	89	65	G 2 ½	49	0,560	40414533		A
75=B	89	65	G 2 ½	49	0,600	30330033	with locking device	A
75=B-DS	89	64	G 2 ½	37	1,100	40342046		A
75=B	89	65	G 3	80	0,650	60157333		A
75=B	89	65	G 3	80	0,700	60433033	with locking device	A
100	115	88	G 4	78	1,150	40379633		A
110=A-DS	133	100	G 4	68	1,475	30233733		A

Nominal size	Lug spacing b (mm)	Inside dia. d (mm)	Female thread W	Face-to-face length L (mm)	Weight (kg)	Ident.No.	Remarks	Alloy
110=A-DS	133	100	G 4	68	1,500	60343133	with locking device	A
110=A-DS	133	100	G 4	55	3,200	40458346		A
110=A-DS	133	100	G 4 ½	84	1,485	60462533		A
125	148	98	G 4	78	1,935	30287933		A
125-DS	148	115	G 5	105	2,200	60345533		A
150-DS	160	130	G 6	116	3,100	30378433	3 lugs	A

Other sizes and styles on request.