


Clamp fittings with threaded tail useable for pipes, fittings and appliances, when these appliances and fittings are to be held in a certain position i.e. when they must not turn during coupling.

- Aluminium alloys (A)
- High grade steel (St)

Clamp fittings swivelling with male threaded tail end



1101



1101

Nominal size	Lug spacing b (mm)	Inside dia. d (mm)	Male thread W	Face-to-face length L (mm)	Weight (kg)	Ident.No.	Remarks	Alloy
52=C	66	45	G 2 A	52	0,375	50194533		A
52=C-DS	66	45	G 2 A	52	0,375	60226933		A
52=C	66	45	G 2 A	52	0,375	60265833	with locking device	A
52=C	66	45	G 2 A	70	0,400	50256433		A
52=C	66	45	G 2 A	70	0,400	60268633	with locking device	A
65	81	57	G 2½ A	35	0,480	50194633		A
75=B	89	64	G 2½ A	40	0,495	50194833		A
75=B	89	58	G 2½ A	50	0,625	30262533	with locking device	A
90-DS	105	76	G 3 A	44	0,700	50194933		A
100	115	88	G 4 A	74	1,145	40342533		A
110=A-DS	133	100	G 4 A	44	1,160	50195133		A
110=A-DS	133	100	G 4 A	44	1,200	60529233	with locking device	A
125	148	98	G 4 A	56	1,400	50195233		A
125	148	98	G 4 A	56	1,480	60610633	with locking device	A
125	148	115	G 5 A	85	2,110	60170333		A

Nominal size	Lug spacing b (mm)	Inside dia. d (mm)	Male thread W	Face-to-face length L (mm)	Weight (kg)	Ident-No.	Remarks	Alloy
125	148	100	G 5 A	85	2,235	60503733	with locking device	A

Other sizes and styles on request.