


A non-symmetrical quick connection coupling with a male and female part. These couplings are only suitable for delivery operation. For suction operation round thread couplings are in use.

- Aluminium alloys (A)
- Copper alloys (C)

Delivery hose couplings Instantaneous



1010



1010

| Nominal size (inch) | For hose i. d. inch (mm) | Weight (kg) | Ident.No. | Remarks | Alloy |
|---------------------|--------------------------|-------------|-----------|----------------|-------|
| 1 1/2" | 1 1/2" (38) | 0,410 | 30227632 | multi-serrated | A |
| 1 1/2" | 1 1/2" (38) | 1,380 | 30227693 | multi-serrated | A |
| 2 1/2" | 1 1/2" (38) | 0,950 | 30226232 | | A |
| 2 1/2" | 1 1/2" (38) | 2,750 | 40339495 | | A |
| 2 1/2" | 1 3/4" (45) | 1,000 | 30245233 | | A |
| 2 1/2" | 1 3/4" (45) | 2,800 | 40074993 | | A |
| 2 1/2" | 2" (52) | 0,960 | 30204433 | | A |
| 2 1/2" | 2" (52) | 2,800 | 40098193 | | A |
| 2 1/2" | 2 1/2" (64) | 0,980 | 30203733 | | A |
| 2 1/2" | 2 1/2" (64) | 2,800 | 40144693 | | A |
| 2 1/2" | 2 3/4" (70) | 1,050 | 30053633 | | A |
| 2 1/2" | 2 3/4" (70) | 2,800 | 40077893 | | A |
| 2 1/2" | 3" (75) | 1,100 | 60654333 | | A |

As per: 19.12.2011