

Couplings according French Standard

A symmetrical quick connection coupling with and without locking ring. Firebrigades are mainly using quick connection couplings type DSP (NF S 61 704) and AR (NF S 61 705), for industrial application generally couplings type Guillemain (NF 29 572) are in use. Identical sizes of the different systems can be matched. To illustrate the fitting possibilities.

- Aluminium alloys (A)
- Copper alloys (C)
- High grade steel (St)

Adapters DSP and AR without locking ring



1220 B

| Nominal size | Lug spacing b (mm) | Female thread | Male thread | Weight (kg) | Ident.-No. | Remarks | Alloy |
|--------------|--------------------|---------------|-------------|-------------|------------|---------|-------|
| 40 | 55 | G 1½ | | 0,095 | 60205033 | | A |
| 40 | 55 | | G 1½ A | 0,120 | 60205133 | | A |
| 40 | 55 | G 2 | | 0,150 | 30226932 | | A |
| 40 | 55 | | G 2 A | 0,200 | 60163433 | | A |
| 65 | 84 | G 2 | | 0,250 | 60424633 | | A |
| 65 | 84 | G 2½ | | 0,200 | 60162533 | | A |
| 65 | 84 | | G 2½ A | 0,200 | 60164733 | | A |
| 65 | 84 | G 3 | | 0,400 | 60205233 | | A |
| 65 | 84 | | G 3 A | 0,350 | 60205333 | | A |
| 100 | 123 | G 4 | | 0,650 | 60198833 | Type AR | A |
| 100 | 123 | | G 4 A | 1,200 | 60150733 | Type AR | A |
| 100 | 123 | G 4½ | | 1,210 | 60185733 | Type AR | A |

As per: 22.03.2010