

A symmetrical quick connection coupling with and without locking ring. Firebrigades are mainly using quick connection couplings type DSP (NF S 61 704) and AR (NF S 61 705), for industrial application generally couplings type Guillemain (NF 29 572) are in use. Identical sizes of the different systems can be matched. To illustrate the fitting possibilities.

- Aluminium alloys (A)
- Copper alloys (C)
- High grade steel (St)

Adapters Guillemain with locking ring



1220 C

Nominal size	Lug spacing b (mm)	Female thread	Male thread	Weight (kg)	Ident.-No.	Remarks	Alloy
20	32	G ¾		0,070	60301133		A
20	32		G ¾ A	0,070	60301233		A
25	37,5	G 1		0,090	60301333		A
25	37,5		G 1 A	0,090	60301433		A
40	55	G 1½		0,205	60438533		A
40	55		G 1½ A	0,150	60515033		A
40	55	G 2		0,240	60515133		A
50	69	G 2		0,340	60301533		A
50	69	G 2		0,930	60301593		A
50	69	G 2		0,750	60301546		A
50	69		G 2 A	0,250	60286733		A
50	69		G 2 A	0,640	60286793		A
50	69		G 2 A	0,820	60286746		A
65	84	G 2		0,350	60220933		A
65	84	G 2½		0,450	60339633		A

Nominal size	Lug spacing b (mm)	Female thread	Male thread	Weight (kg)	Ident.-No.	Remarks	Alloy
65	84		G 2½ A	0,320	60354933		A
80	103	G 2½		0,600	60658933		A
80	103	G 3		0,725	60257733		A
80	103	G 3		1,980	60257793		A
80	103	G 3		1,600	60407046		A
80	103		G 3 A	0,500	60301633		A
80	103		G 3 A	1,300	60301693		A
80	103		G 3 A	1,600	60301646		A
100	123	G 4		1,100	60301733		A
100	123	G 4		3,150	60301795		A
100	123	G 4		4,350	60301746		A
100	123		G 4 A	0,820	60196433		A
100	123		G 4 A	3,000	60196495		A
100	123		G 4 A	2,160	60196446		A
150	190	G 6		3,390	60559633		A
150	190		G 6 A	3,120	60559733		A