

Couplings according French Standard

A symmetrical quick connection coupling with and without locking ring. Firebrigades are mainly using quick connection couplings type DSP (NF S 61 704) and AR (NF S 61 705), for industrial application generally couplings type Guillemain (NF 29 572) are in use. Identical sizes of the different systems can be matched. To illustrate the fitting possibilities.

- Aluminium alloys (A)
- Copper alloys (C)
- High grade steel (St)

Adapters Guillemain without locking ring



1220 D

Nominal size	Lug spacing b (mm)	Female thread	Male thread	Weight (kg)	Ident.-No.	Remarks	Alloy
20	32	G ¾		0,040	60300633		A
25	37,5	G 1		0,040	60277933		A
25	37,5		G 1 A	0,050	60300833		A
40	55	G 1½		0,075	60339533		A
40	55	G 1½		0,200	60339593		A
40	55	G 2		0,155	60162933		A
40	55	G 2		0,470	60162993		A
50	69	G 2		0,160	60149533		A
50	69	G 2		0,360	60149593		A
50	69	G 2		0,310	60149546		A
50	69		G 2 A	0,150	60300933		A
50	69		G 2 A	0,490	60300993		A
50	69		G 2 A	0,530	60300946		A
65	84	G 2½		0,150	60149333		A
65	84	G 2½		0,470	60149393		A

Nominal size	Lug spacing b (mm)	Female thread	Male thread	Weight (kg)	Ident.-No.	Remarks	Alloy
65	84	G 2½		0,400	60149346		A
65	84		G 2½ A	0,240	60191933		A
65	84		G 2½ A	0,700	60191993		A
65	84		G 2½ A	0,950	60191946		A
80	103	G 3		0,250	60286833		A
80	103	G 3		0,800	60286893		A
80	103	G 3		0,900	60286846		A
80	103		G 3 A	0,300	60301033		A
80	103		G 3 A	1,000	60301093		A
80	103		G 3 A	1,120	60301046		A
100	123	G 4		0,400	60287033		A
100	123	G 4		1,100	60287093		A
100	123	G 4		0,900	60287046		A
100	123		G 4 A	0,600	60192033		A
100	123		G 4 A	1,500	60192093		A
100	123		G 4 A	0,600	60192046		A