


A symmetrical quick connection coupling with and without locking ring. Firebrigades are mainly using quick connection couplings type DSP (NF S 61 704) and AR (NF S 61 705), for industrial application generally couplings type Guillemain (NF 29 572) are in use. Identical sizes of the different systems can be matched. To illustrate the fitting possibilities.

- Aluminium alloys (A)
- Copper alloys (C)
- High grade steel (St)

Delivery- and suction couplings Guillemain with locking ring



1020 B



1020 B

Nominal size	Lug spacing b (mm)	For hose i. d. D (mm)	Weight (kg)	Ident-No.	Remarks	Alloy
20	32	25	0,050	60271433		A
40	55	45	0,150	60164933		A
40	55	45	0,495	60164993		A
50	69	51	0,300	60286533		A
50	69	51	1,000	60286593		A
50	69	51	0,800	60286546		A
50	69	55	0,300	60300333		A
65	84	65	0,350	60524733		A
65	84	65	1,070	60524793		A
65	84	65	0,800	60524746		A
65	84	70	0,450	60164833		A
65	84	70	1,500	60164895		A
65	84	70	1,200	60164846		A
80	103	75	0,700	60286633		A

Nominal size	Lug spacing b (mm)	For hose i. d. D (mm)	Weight (kg)	Ident-No.	Remarks	Alloy
80	103	75	2,100	60286695		A
80	103	75	1,800	60286646		A
80	103	90	0,700	60300433		A
80	103	90	2,100	60300493		A
80	103	90	1,800	60300446		A
100	123	100	1,000	60257833		A
100	123	100	3,000	60257893		A
100	123	100	2,500	60257846		A
100	123	110	1,100	60300533		A
100	123	110	3,500	60300595		A
100	123	110	3,000	60300546		A
150	190	150	3,450	60443033		A