

Quick Connection Couplings Storz System for Liquids, Powders and Granulates

Symmetrical quick connection coupling, no female and male part, no problem with matching hose ends. Assembly and functionality of couplings Storz System.

Quick connection couplings with DS suffix generally are suitable for delivery and suction operation, without DS suffix for delivery operation only.

Working pressure is PN 16 if not mentioned otherwise.

- Aluminium alloys (A)
- Copper alloys (C)
- High grade steel (St)

Hose binders PERFEKT



1009 E

Used to seal damaged hoses. Made of spring-loaded steelband with Cellular rubber and buckle.

For hose i. d. (mm)	Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Ident.No.	Alloy
38	160	76	20	0,115	60100544	A
42	170	76	20	0,110	60147244	A
45	180	76	20	0,110	60195444	A
52=C	200	76	20	0,140	60020844	A
55	210	76	20	0,145	60169244	A
65	240	76	20	0,150	60100644	A
70	260	76	20	0,140	60178244	A
75=B	280	76	20	0,155	60020944	A
100	350	76	20	0,160	60322944	A
110=A	520	76	20	0,160	60195544	A
125	520	76	20	0,210	60502444	A
150	520	76	20	0,200	60323344	A

