

Symmetrical quick connection coupling, no female and male part, no problem with matching hose ends. Assembly and functionality of couplings Storz System.

Quick connection couplings with DS suffix generally are suitable for delivery and suction operation, without DS suffix for delivery operation only.

Working pressure is PN 16 if not mentioned otherwise.

- Aluminium alloys (A)
- Copper alloys (C)
- High grade steel (St)

Hose couplings with folding handles



1004 A



1004 B

1004 A: The two folding handles fitted to the clamp fitting eliminate the need for a coupling spanner and allow quicker and easier coupling.

1004 B: Size B has one resp. size A two combined coupling and locking handles. By folding the handles and matching the couplings, the coupling is automatically secured.

Nominal size	Lug spacing b (mm)	For hose i. d. (mm)	Length tail piece L (mm)	Inside dia. (mm)	Weight (kg)	Ident.No.	Remarks	Alloy
75=B-DS	89	75	125	62	0,850	60334933	Style 1004 B	A
100-DS	115	101	150	90	1,545	60331333		A
110=A-DS	133	100	170	90	2,210	60259433		A
110=A-DS	133	100	170	90	1,945	60539333	Style 1004 B	A
110=A-DS	133	110	170	100	2,200	60259533		A
110=A-DS	133	110	170	100	1,700	60188933	for Scharfenberg ²⁾	A
125-DS	148	125	197	113	2,405	60325333		A
150-DS	160	150	180	130	3,025	60328433	3 lugs	A

As per: 04.01.2012