

Symmetrical quick connection coupling, no female and male part, no problem with matching hose ends. Assembly and functionality of couplings Storz System.

Quick connection couplings with DS suffix generally are suitable for delivery and suction operation, without DS suffix for delivery operation only.

Working pressure is PN 16 if not mentioned otherwise.

- Aluminium alloys (A)
- Copper alloys (C)
- High grade steel (St)

Quick binding, hose clamps according DIN 2817 (2 parts with screws and nuts)



1007

Suitable for heavy-wall rubber hoses.

Nominal size	Outside dia. of binding D (mm)	Lug spacing b (mm)	For hose i. d. D (mm)	Inside dia. d (mm)	Weight (kg)	Ident.-No.	Remarks	Alloy
25=D-DS		31	25,4	20	0,090	60669333		A
25=D	36 - 39		25		0,140	60669433	hose clamp	A
52=C-DS		66	32,4	25	0,400	60555633		A
52=C	43 - 46		32		0,140	60556733	hose clamp	A
52=C-DS		66	38,4	32	0,400	60555533		A
52=C	50 - 52		38		0,160	60556833	hose clamp	A
52=C-DS		66	50,4	45	0,600	60505933		A
52=C-DS		66	50,4	45	0,700	60530733	seal silicone	A
52=C	64 - 67		50		0,270	60556933	hose clamp	A
75=B-DS		89	63,4	55	0,660	60556233		A
75=B	78 - 82		65		0,400	60557033	hose clamp	A
75=B-DS		89	75,4	71,5	0,700	60562733		A
75=B-DS		89	75,4	71,5	0,755	60478433	with locking device	A

Nominal size	Outside dia. of binding D (mm)	Lug spacing b (mm)	For hose i. d. D (mm)	Inside dia. d (mm)	Weight (kg)	Ident.No.	Remarks	Alloy
75=B-DS		89	75,4	71,5	0,800	60562833	seal silicone	A
75=B	89 - 93		75		0,490	60557133	hose clamp	A
100-DS		115	100,3	90	1,160	60549333		A
110=A-DS		133	100,3	96	1,580	60537933		A
110=A-DS		133	100,3	90	1,605	60506833	with locking device	A
100-DS / 110=A	114-119		100		1,100	60557233	hose clamp	A

Other sizes and styles on request.