

## Extinguishing Bucket

Very reliable as piston pump works in both directions. Suitable for extinguishing starting fires of class A. The bucket will be emptied in less than one minute.

### Available styles:

**A-10/3900** Jet nozzle DK DIN 14 405 and adapters DIN 14 306 resp. coupl. DIN 14 301, hose 5 m, D 25 DIN 14811. Synthetic, internally rubber coated.

**B-10/3901** Screws copper alloy, hose 1 m, 1/2" i. d. PVC, nozzle polyamide.

### Extinguishing Bucket



3900

Very reliable as piston pump works in both directions. Suitable for extinguishing starting fires of class A. The bucket will be emptied in less than one minute.

### Available styles:

**A-10/3900** Jet nozzle DK DIN 14 405 and adapters DIN 14 306 resp. coupl. DIN 14 301, hose 5 m, D 25 DIN 14811. Synthetic, internally rubber coated.

**B-10/3901** Screws copper alloy, hose 1 m, 1/2" i. d. PVC, nozzle polyamide.



3901

Style / Nominal size	Outside Ø base (mm)	Volume (Ltr.)	Height (mm)	Weight (kg)	Style	Ident-No.	Remarks
A 10	200	10	663	7,600	3900	60210444	DIN 14 405
A 10	200	10	663	6,500	3900	60483144	without hose
B 10	200	10	663	6,400	3901	60483344	DIN 14 405

As per: 19.12.2011