

Dividers are used for distributing the extinguishing medium from one feed line over several hose lines, or in special cases for collecting it in the reverse direction. Each hose line can be shut-off individually by means of a stop valve. The stop valve of the dividers must be according to DIN 14365 easily operated in the usual flow direction at 16 bar and in the opposite direction at 6 bar.

Dividers with screw down valves - 3 outlets



3101

Allows smooth opening and closing and can be used as a regulating element.

Storz System Connection or thread

Inlet Storz / thread	Outlet Storz / thread	Bonnets inch	Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Ident.-No.	Remarks
C	2 x D + C	2 x 1" + 2"	280	250	230	2,350	10027033	DIN 14 345
G 2 A	2 x G 1 A + G 2 A	2 x 1" + 2"	240	250	230	1,650	60166133	
65	3 x 38	2 x 2" + 2½"	240	260	230	4,900	60124833	
65	2 x 38 + 65	2 x 2" + 2½"	240	260	230	5,100	60186833	
65	3 x 65	2 x 2" + 2½"	340	400	260	5,400	60509033	
65	3 x 65	2 x 2" + 2½"	340	400	260	5,400	60181133	¹⁾
B	3 x C	2 x 2" + 2½"	335	400	260	5,060	60022533	
B	2 x C + B	2 x 2" + 2½"	360	400	260	5,900	60024233	³⁾ DIN 14 345
B	2 x C + B	2 x 2" + 2½"	340	400	260	5,250	10028833	
B	2 x C + B	2 x 2" + 2½"	340	400	260	5,250	60540633	⁴⁾
B	2 x C + B	2 x 2" + 2½"	340	400	260	14,000	10029893	
G 2½ A	2 x G 2 A + G 2½ A	2 x 2" + 2½"	300	400	260	3,610	10040433	

As per: 19.12.2011