

Dividers are used for distributing the extinguishing medium from one feed line over several hose lines, or in special cases for collecting it in the reverse direction. Each hose line can be shut-off individually by means of a stop valve. The stop valve of the dividers must be according to DIN 14365 easily operated in the usual flow direction at 16 bar and in the opposite direction at 6 bar.

Dividers with ball valves - 2 outlets



3200

They have a straight free-flow waterway, very low friction loss and easy and quick controllability.

Storz System Connection or thread

Inlet-Storz / thread	Outlet-Storz / thread	Balls ND (mm)	Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Ident-No.	Remarks
D	2 x D	2 x 20	180	145	105	0,900	30127233	
G 1 A	2 x G 1 A	2 x 20	152	115	105	0,720	60144033	
C	2 x D	2 x 20	185	145	125	1,100	60134333	
C	2 x C	2 x 40	270	370	221	2,900	30129133	1)
65	2 x 38	2 x 40	265	370	221	2,800	20174933	1)
65	2 x 45	2 x 40	265	370	221	3,050	60255933	1)
65	2 x 65	2 x 40	275	370	221	3,200	60167433	1)
B	2 x C	2 x 40	275	370	221	3,050	30170333	1)
G 2½	2 x G 1½	2 x 32	205	165	190	1,490	60645033	
G 2 A	2 x G 2 A	2 x 40	235	370	221	2,100	60141333	1)
G 2½ A	2 x G 2 A	2 x 40	200	370	221	2,100	20204933	1)
G 2½ A	2 x G 2½ A	2 x 50	270	230	240	4,040	20210833	
B	2 x B	2 x 40	275	370	221	3,400	20157233	1)
A	2 x 65	2 x 50	310	286	265	6,200	60609233	
A	2 x B	2 x 50	310	286	265	6,000	20156333	
G 4 A	2 x G 2½ A	2 x 50	270	225	265	4,000	60156233	

