

## Dividers

Dividers are used for distributing the extinguishing medium from one feed line over several hose lines, or in special cases for collecting it in the reverse direction. Each hose line can be shut-off individually by means of a stop valve. The stop valve of the dividers must be according to DIN 14365 easily operated in the usual flow direction at 16 bar and in the opposite direction at 6 bar.

### Dividers with ball valves - 3 outlets



3231

With 3 outlets and one inlet. They have a straight free-flow waterway, very low friction loss and easy and quick controllability.

#### North-American Standard Connection

Inlet	Outlet	Balls ND (mm)	Weight (kg)	Ident.No.	Remarks
G 5 A	3 x 2½" m	3 x 50	7,100	10047433	
G 5 A	3 x 2½" m	3 x 50	8,640	10047401	1)
100	3 x 2½" f	3 x 50	9,800	60380533	
100	3 x 2½" m	3 x 50	8,300	60380633	
100	3 x 2½" QST-m	3 x 50	10,000	60584501	1)
125	3 x 2½" f	3 x 50	10,300	60380733	
125	3 x 2½" m	3 x 50	8,600	60380833	
125	2 x 2½" m + Storz 100	2 x 50 + 100	16,000	60561733	
G 5 A	2 x 2½" m + G 4 A	2 x 50 + 100	13,800	10067433	

As per: 04.04.2010