

AWG-Turbo-Nozzles meet the standard DIN 14 367 for branchpipes. The flow rates can be selected by the adjusting sleeve, and opening and closing by means of the lever. A special feature is the extinguishing power, due to optimal droplet size also at the full range of the 0° to 120° adjustable water-filled spray stream. The AWG-Nozzles have two pointers, a good aid to feel the selected flow rate as well as the type of the stream. With Flash-Over position. Inlet also swivelling under pressure.

Information about the test results and approvals for AWG-Nozzles as well as the possibility to use them on electrical installations is available upon request.

- Aluminium alloys (A)
- Copper alloys (C)

Turbo-Nozzle Non-Corrosive



4300 E

Light aluminium with coating for protection against corrosion. A 25 my tin layer makes this nozzle **sea water resistant** .

Inlet Storz thread swivelling	Type	Flow rate selection l/min / 6 bar	Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Style	Ident-No.	Alloy
C	2130	40-80-130	265	98	230	1,600	4300 A	10073785	A
C	2400	130-235-400	290	115	245	2,500	4300 C	10071885	A
B	2750	360-550-750	405	126	245	3,600	4300 D	20208885	A

Additional styles and sizes on request.