

AWG-Turbo-Nozzles meet the standard DIN 14 367 for branchpipes. The flow rates can be selected by the adjusting sleeve, and opening and closing by means of the lever. A special feature is the extinguishing power, due to optimal droplet size also at the full range of the 0° to 120° adjustable water-filled spray stream. The AWG-Nozzles have two pointers, a good aid to feel the selected flow rate as well as the type of the stream. With Flash-Over position. Inlet also swivelling under pressure.

Information about the test results and approvals for AWG-Nozzles as well as the possibility to use them on electrical installations is available upon request.

- Aluminium alloys (A)
- Copper alloys (C)

Turbo-Nozzle 2235 / 2950



4310

British Standard BS 336 Connection, Instantaneous

Inlet swivelling	Type	Flow rate selection l / min at 6 bar	Weight (kg)	Style	Ident-No.	Remarks	Alloy
1 ½" m	2235	60-130-235	2,200	4300 B	60584633		A
2 ½" m	2235	60-130-235	2,430	4300 B	60578833		A
2 ½" m	2400	130-135-400	2,480	4300 C	60578933		A
2 ½" m	2750	360-550-750	3,500	4300 D	60618033		A
2 ½" m	2950	550-750-950	3,500	4300 D	60618133		A

As per: 19.12.2011