

- Aluminium alloys (A)
- Copper alloys (C)

Gate valves with 25° elbow and pressure relief valve



6502

Nominal size	Inlet Storz / thread	Outlet Storz / thread ¹⁾	Inside dia. d (mm)	Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Ident.No.	Remarks	Alloy
100	G 4 A	G 4	95	236	150	393	8,100	20408633	Basic model	A
100	G 4 A	G 4	95	245	150	395	7,680	20204833	Outlet straight	A
100	100	NH 4"	95	270	156	420	10,700	60376933		A
100	100	NH 4½"	95	270	156	420	10,400	60377033		A
100	100	NH 5"	95	270	156	420	10,700	60377133		A
100	100	NH 6"	95	270	156	420	11,300	60377233		A
100	100	Storz 100	89	305	156	420	9,700	60377333		A
100	125	NH 4"	95	290	196	442	10,900	60377433		A
100	125	NH 4½"	95	290	196	442	10,600	60377533		A
100	125	NH 5"	95	290	196	442	10,900	60377633		A
100	125	NH 6"	95	290	196	442	11,500	60377733		A
100	125	Storz 125	95	330	196	442	9,900	60377833		A
130	150	164 AD	130	320	220	435	17,100	60671033	3 lugs, with locking device	A