

- Aluminium alloys (A)
- Copper alloys (C)

Gate valves with straight bore



6500-2 1/2"

Shut-off valve for pressure- or suction hose lines, double sealed, non rising stem, with air-bleeder and built-in filtering screen at the inlet, handwheel with solid grip, approx. 8 turns for complete shut down and opening. Style 6500-2 1/2" with a usual handwheel, w/o grip.

Storz System Connection or thread



6500-4"



6500-6"

Nominal size	Inlet Storz / thread	Outlet Storz / thread ¹⁾	Inside dia. d (mm)	Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Ident.-No.	Remarks	Alloy
65	G 2 1/2 A	G 2 1/2	63	85	110	225	1,350	30395033		A
65	AD 79	2 1/2" NH-male	63	85	110	295	1,400	30395002	²⁾	A
65	G 2 1/2	G 2 1/2	63	105	110	225	1,800	60594833		A
100	G 4 A	G 4	95	190	150	393	5,500	20452833	Basic model	A
100	100	NH 4"	95	215	156	396	8,100	60375033		A
100	100	NH 4 1/2"	95	215	156	396	7,800	60359833		A
100	100	NH 5"	95	215	156	396	8,100	60375133		A
100	100	NH 6"	95	215	156	396	8,700	60375233		A
100	100	Storz 100	89	250	156	396	7,100	60375333		A
100	125	NH 4"	95	228	196	416	8,800	60375433		A
100	125	NH 4 1/2"	95	228	196	416	8,500	60375533		A
100	125	NH 5"	95	228	196	416	8,800	60375633		A
100	125	NH 6"	95	228	196	416	9,400	60375733		A
100	125	Storz 125	95	279	196	416	8,400	60375833		A
130	G 6 A	G 6 A	130	180	220	480	13,500	20207833		A

